



BPI COMPONENT GUIDE:

SPORTING 20 SHORT

WWW.BALLISTICPRODUCTS.COM

The SG20-S is designed to accommodate bulky powders, large shot payloads or low-volume, taper-interior hulls. The shotcup of the SG20-S is the same depth as the SG20-L.

The cushion section of the SG20-S is comprised of a large tubular reducer that accommodates many different load heights and offers excellent inertia absorption during the firing process.

The best range for the SG20-S is approximately 25-45 yards, making it a great wad for upland game hunters and clays shooters alike. Our best results tend to be with 7/8-ounce lead loads although we often use 1 ounce of #6 or #7 for hunting loads.

“★★★★★ - **Great short wad** I reload for cowboy action shooting with Triple Se7en powder which is bulky. These short wads give me enough room for a good charge and a full 7/8 oz payload. Plus the plastic snot comes out of the barrel easily when cleaning.” - George, TX

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications.

Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and “Load of the Week” at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.335"
DIAMETER:	0.610"
SHOTCUP DEPTH:	0.760"
SEAL TO CUP BOTTOM:	0.575"
THICKNESS:	0.025"



LD20SG20S




WARNING


Cancer and Reproductive Harm
- www.P65Warnings.ca.gov

LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
20-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP															
60919-59	20	Fiocchi	Fio616	Longshot	20.0		SG20S		N720	7/8	382.8	Lead		8500	1275
20-GAUGE • 2-1/2" LENGTH • BISMUTH SHOT • ROLL CRIMP															
11511	20	Cheddite	Ched209	Longshot	18.0		SG20S		OS20	7/8	382.8	Bismuth		8625	1180
11512	20	Cheddite	Ched209	Longshot	19.6		SG20S		OS20	7/8	382.8	Bismuth		9800	1263

OTHER USEFUL COMPONENTS



20GA 1/8" MAXI-NITRO CARD
NC20 | #NC20



20GA OVERSHOT CARDS
OS20 | #OS20



32GA 1/4" CORK WADS
14CW32 | #14CW32



20GA 1/8" FELT WADS
18FW20 | #1221820



20GA 1/4" FELT WADS
14FW20 | #1221420

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. **We recommend 32ga cork or 20ga felt fillers for inside the 20 gauge wads (felt is soft and can be forced into the base of the wad).**

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.