



BPI COMPONENT GUIDE:

28GA BRUSH WAD

WWW.BALLISTICPRODUCTS.COM

The Brush Wad is a symmetrical cushioned platform with very short shotcup. This design enhances wider patterns and improved short-range performance with a peripheral shot spread. Brush Wads are very consistent in our lab testing. Try Brush Wads and open up a whole new pattern potential from your shotgun at short range.

We like to use this wad with an Overshot Card or two for highly effective short-range spreader loads (from 5-25 yard).

Optimum range: 10-35 yards Short range, springing targets and overhead shots, upland hunting.

“★★★★★ - **QUAIL** Quail hunters this is the wad you need for those ranges 10 to 30 yards in thick cover. The patterning board will show you the results.” - James, NV

RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and “Load of the Week” at www.ballisticproducts.com**



TECHNICAL SPECS:

OVERALL LENGTH:	1.205"
DIAMETER:	0.560"
SHOTCUP DEPTH:	0.224"
SEAL TO CUP BOTTOM:	0.990"
THICKNESS:	0.038"



LD28BW28




WARNING

Cancer and Reproductive Harm
- www.P65Warnings.ca.gov


LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
28-GAUGE • 2-1/2" LENGTH • LEAD SHOT • ROLL CRIMP															
230607-11878	28	Fiocchi	Fio616	Universal	13.0		BW28		0S28	5/8	273.4	Lead #7.5		7000	1175
101115-2569M	28	Fiocchi	Fio616	Longshot	12.2		BW28		0S28	3/4	328.1	NP Lead #6.5		6900	1000
28-GAUGE • 2-3/4" LENGTH • LEAD SHOT • ROLL CRIMP															
101115-2577	28	Fiocchi	Fio616	Universal	15.0		BW28		0S28	3/4	328.1	NP Lead #6.5		9300	1200
28-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP															
90720-1048	28	Fiocchi	Fio616	Unique	19.0	NC28	BW28			1/2	218.8	Lead		11100	1660
120907-4224	28	Cheddite	Ched209	Alliant 20/28	16.0		BW28			3/4	328.1	Lead #8		11500	1350
230607-11881	28	Fiocchi	Fio616	Alliant 20/28	16.0		BW28		0S28	3/4	328.1	Lead #7.5		10760	1300

OTHER USEFUL COMPONENTS

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. We recommend .410 & .430 Bore fillers for inside the 28 gauge wads.



28GA 1/8" MAXI-NITRO CARD
NC28 | #NC 28



28GA OVERSHOT CARDS
0S28 | #0S 28



.410 1/2" FIBER WAD
FC410 | #FC 410
.430 1/2" FIBER WAD
FC430 | #FC 430

WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.