



BPI COMPONENT GUIDE:

# ORIGINAL SPORTING 28

WWW.BALLISTICPRODUCTS.COM

The original Sporting-28. The SG28 permits light, fast-moving loads for skeet, sporting clays, or game. Many loads are perfect ratios for quail, dove, and “reaching” grouse.

“★★★★★ - **Essential for Fiocchi, Cheddite, Riefenhauser type hulls** This is the only wad that will afford you a good flat crimp with conventional 3/4 oz.loads in 2 3/4 hulls such as Fiocchi low basewad, Rio, Cheddite, Kent etc. This was the original wad used in Fiocchi/Dionisi factory loads.”  
- Todd, WI

## RECOMMENDED MANUALS

There is so much more to shotshell reloading than just the load data. Safety is your TOP priority. In order to become a safe and competent reloader, one must continue the learning process by reading and researching. Don't try to outsmart the instructions! We offer over a half century of loading knowledge, wit, and wisdom in our publications. Our manuals are continually upgraded with new data and the latest tools and techniques. Available in print version or downloads from our website. **Therefore, we encourage you to master the information in our manuals, brochures, and “Load of the Week” at [www.ballisticproducts.com](http://www.ballisticproducts.com)**



### TECHNICAL SPECS:

OVERALL LENGTH:	1.497"
DIAMETER:	0.550"
SHOTCUP DEPTH:	0.554"
SEAL TO CUP BOTTOM:	0.920"
THICKNESS:	0.035"



LD28SG28



**WARNING**

Cancer and Reproductive Harm  
- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)


LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRNS.	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	OVER SHOT	SHOT (OZ.)	SHOT (GRNS.)	SHOT SIZE	BUFFER (GRAINS)	PSI	FPS
<b>28-GAUGE • 2-3/4" LENGTH • LEAD SHOT • ROLL CRIMP</b>															
101115-2578	28	Cheddite	Ched209	Longshot	16.5		SG28		OS28	3/4	328.1	NP Lead #6.5		9600	1295
101115-2579	28	Fiocchi	Fio616	HS-6	19.0		SG28		OS28	3/4	328.1	NP Lead #6.5		10000	1295
<b>28-GAUGE • 2-3/4" LENGTH • LEAD SHOT • FOLD CRIMP</b>															
121221-4467SK	28	Cheddite	Ched209	700-X	12.1		SG28			3/4	328.1	Lead #8		11200	1200
130826-4986	28	Cheddite	Ched209	Alliant 20/28	16.0		SG28			3/4	328.1	Lead #8		11400	1320
130103-4471	28	Cheddite	Ched209	Clays	10.0		SG28		OS28	3/4	328.1	Lead #8		10600	1070
230607-11875	28	Cheddite	Ched209	Longshot	14.5		SG28		OS28	3/4	328.1	Lead #7.5		8150	1200
130826-4983	28	Cheddite	Ched209	Pro Reach	14.0		SG28			3/4	328.1	Lead #8		8900	1170
130826-4982	28	Cheddite	Ched209	Pro Reach	16.0		SG28			3/4	328.1	Lead #8		10500	1290
121220-4466SK	28	Cheddite	Ched209	Red Dot	12.0		SG28			3/4	328.1	Lead #8		11400	1200
90909-1302	28	Fiocchi	Fio616	Alliant 20/28	16.0		SG28			3/4	328.1	Lead		11400	1335
60801-HOD15	28	Winchester AA HS	Win209	Longshot	14.4		SG28			3/4	328.1	Lead		9200	1200
170620-9465	28	Fiocchi	Fio616	Alliant 20/28	12.0		SG28			7/8	382.8	Lead #7.5		10200	1115

## OTHER USEFUL COMPONENTS

Filler & cushion wads occupy space below the pellets so that the load can be crimped properly. Remember, different payloads and different pellet sizes occupy different volumes, so you will want an assortment of sizes on hand. Overshot cards improve overall crimp quality and seal in small shot and/or buffer. We recommend .410 & .430 Bore fillers for inside the 28 gauge wads.



**28GA 1/8" MAXI-NITRO CARD**  
NC28 | #NC 28



**28GA OVERSHOT CARDS**  
OS28 | #OS 28



**.410 1/2" FIBER WAD**  
FC410 | #FC 410  
**.430 1/2" FIBER WAD**  
FC430 | #FC 430

**WARNING:** BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".

ITALICIZED COMPONENTS ARE NO LONGER IN PRODUCTION, BUT MAY STILL BE FOUND IN CIRCULATION. CONSULT YOUR RELOADING MANUAL FOR ADDITIONAL DETAILS AND INFORMATION.